

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
29 April 2004 (29.04.2004)

PCT

(10) International Publication Number
WO 2004/036818 A1

(51) International Patent Classification⁷: H04L 1/18, 27/34

(74) Agent: KUHL, Dietmar; Grünecker, Kinkeldey, Stockmair & Schwanhäußer Anwaltszietät, Maximilianstrasse 58, 80538 München (DE).

(21) International Application Number:

PCT/EP2002/011694

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 18 October 2002 (18.10.2002)

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(25) Filing Language: English

(26) Publication Language: English


(71) Applicant (*for all designated States except US*): MAT-SUSHITA ELECTRIC INDUSTRIAL CO., LTD. [JP/JP]; 1006, Kadoma, Kadoma City, Osaka 571-8500 (JP).

Published:

— with international search report

[Continued on next page]

(54) Title: CONSTELLATION REARRANGEMENT FOR ARQ TRANSMIT DIVERSITY SCHEMES



WO 2004/036818 A1

(57) Abstract: An ARQ (re-) transmission method of transmitting data in a wireless communication system wherein data packets are transmitted from a transmitter to a receiver, using a first transmission and a second transmission based on a repeat request. The method comprises the steps of modulating data at the transmitter using a first signal constellation pattern to obtain a first data symbol. The first data symbol is transmitted as the first transmission to the receiver using a first diversity branch. Further, the data is modulated at the transmitter using a second signal constellation pattern to obtain a second data symbol. Then, the second data symbol is transmitted as the second transmission to the receiver over a second diversity branch. Finally, the received first and second data symbol data symbol are diversity combined at the receiver. The invention further relates to a transmitter and a receiver embodied to carry out the method of the invention.

WO 2004/036818 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.